



Product Overview

Catco catalytic heaters bring fuel and oxygen together in the presence of a heated catalyst. This causes a chemical reaction that produces infrared heat but no flame, and the catalyst is not consumed by the reaction. Once it's operational, a catalytic heater can operate indefinitely if it has a clean source of fuel and sufficient air.

The 18x36 heater is most commonly used in space heating applications in remote and/or hazardous locations.



Part Number Key



Heater Configurations


Config	Hazardous Location Listing		Junction Box		Valve and
	Class I Div 1 Group D	Class I Div 2 Group D	Plain	EP	Thermo- couple
-10			•		
-20				•	
-30		FM	•		•
-40	FM	FM		•	•
-50	CSA	CSA		•	•

Product Specs

Fuel


Dating	Fuel Consumption		
Rating BTU/hr (kW)	Natural Gas SCFH (m3/hr)	Propane lb/hr (kg/hr)	
27,000 (7.03)	27.0 (0.76)	1.25 (0.57)	

Electrical



Bus Bar Arrangement		
Parallel Heating Elements (12 V, 120 V)	00	
Series Heating Elements (24 V, 240 V, 480 V)	00	

Starting Amperage, A				
12 V	24 V	120 V	240 V	480 V
33.3	8.3	3.8	1.9	1.9



	Part Number	Description
1	60-007	Facegrill
2	61-024	Reflector
3	30-127	Shutoff valve (aka safety valve)
4	30-010	Thermocouple
5	35-076	Water column pressure gauge
6	40-037-G27000	Thermostat (natural gas)
7	50-005	912 style low pressure regulator
	10-026	Wall-mount brackets (not shown)
	10-073	Floor stand (not shown)

For additional accessories and more information, see the Catalytic Heater Product Bulletin.